

Broadband

Standard											
Frequency (GHz)			Model	Ins Loss (dB max)	Isolation (dB min)	VSWR (max)		Power Fwd (W)	Power Rev (W)	Oper Temp (°C)	Size LxWxT (Inches)
1.0	-	2.0	T1GG1	0.6	18	1.30	:1	10	10	+10 to +40	2.6 X 2.6 X .75
1.5	-	2.7	T1XJ5	0.4	20	1.25	:1	1	1	+10 to +50	2.5 X 2.5 X .75
2.0	-	4.0	T2CV1	0.6	18	1.30	:1	10	10	0 to +50	1.6 X 1.6 X .60
2.0	-	8.0	T2XC2	1.3	10	2.00	:1	10	1	0 to +60	2.0 X 1.86 X .55
4.0	-	8.0	T4YK1	0.6	18	1.30	:1	10	10	0 to +50	1.0 X 1.0 X .60
6.0	-	12.0	T6YL2	0.6	18	1.30	:1	1	1	-20 to +70	.75 X .86 X .51
6.0	-	18.0	T6XD3	1.1	13	1.60	:1	10	1	-54 to +85	.50 X .58 X .38
8.0	-	18.0	T8XM1	0.8	15	1.45	:1	10	1	0 to +70	.50 X .58 X .38
8.0	-	20.0	T8XA2	1.0	15	1.45	:1	10	1	0 to +70	.50 X .68 X .56

* Isolators shown, Circulators and alternate connector and Higher Power configurations available on request